according to Regulation (EC) No. 1907/2006



SPEKTRA RENOXAN FACADE PAINT

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	29.01.2021	MAT0GA00_116 GB / EN	Date of first issue: 29.01.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product code	:	Please see section 16 for detailed data
Trade name	:	SPEKTRA RENOXAN FACADE PAINT
Unique Formula Identifier (UFI)	:	1JV1-T07F-W00Y-YKA7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-	: SU19 Building and construction work
stance/Mixture	Professional and consumer use of coatings, Roller application
	or brushing, Non industrial spraying
	PC9a Coatings and paints, thinners, paint removers

1.3 Details of the supplier of the safety data sheet

Company	: Helios TBLUS d.o.o. Količevo 65 1230 Domžale Slovenia
Telephone Company	: 00386 1 722 4383
Telefax Company	: 1 722 4310
Responsible/issuing person	: 00386 1 722 4383 productsafety@helios.si

1.4 Emergency telephone number

Call 999 for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892 0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)				
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.			
Long-term (chronic) aquatic hazard, Cat- egory 3	H412: Harmful to aquatic life with long lasting effects.			

according to Regulation (EC) No. 1907/2006



SPEKTRA RENOXAN FACADE PAINT

Version Revision Date: SDS Number: 1.0 29.01.2021 MAT0GA00_116 GB / EN	Date of last issue: - Date of first issue: 29.01.2021
--	--

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Labelling (REGULATION (Hazard pictograms	EC) :	No 1272/2008)
Signal word	:	Warning
Hazard statements	:	H317 May cause an allergic skin reaction.H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	:	P101 If medical advice is needed, have product container or label at hand.P102 Keep out of reach of children.
		Prevention:
		P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.P273 Avoid release to the environment.P280 Wear protective gloves.
		Disposal:
		P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

octhilinone (ISO) 1,2-benzisothiazol-3(2H)-one 2-methylisothiazol-3(2H)-one reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3- one (3:1)

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006



SPEKTRA RENOXAN FACADE PAINT

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	29.01.2021	MAT0GA00_116 GB / EN	Date of first issue: 29.01.2021

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature

: Waterborne paint

Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
	Index-No. Registration number		
titanium dioxide	13463-67-7 236-675-5 01-2119489379-17	Carc. 2; H351	>= 1 - < 10
Zinc pyridinethione	13463-41-7 236-671-3	Acute Tox. 3; H301 Acute Tox. 3; H331 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 10	>= 0,025 - < 0,1
octhilinone (ISO)	26530-20-1 247-761-7 613-112-00-5	Acute Tox. 4; H302 Acute Tox. 3; H331 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 specific concentration limit Skin Sens. 1; H317 >= 0,05 %	>= 0,0025 - < 0,025
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	>= 0,0025 - < 0,025

according to Regulation (EC) No. 1907/2006



SPEKTRA RENOXAN FACADE PAINT

ersion 0	Revision Date: 29.01.2021	SDS Nu MATOG GB / EN	A00_116	Date of last issue: - Date of first issue: 29.01.2	021
				specific concentration limit Skin Sens. 1; H317 >= 0,05 %	
2-me	thylisothiazol-3(2H)-	one	2682-20-4 220-239-6 613-326-00-9 01-2120764690-50	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071	>= 0,0025 - 0,025
				M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	
				specific concentration limit Skin Sens. 1A; H317 >= 0,0015 %	
thyl-4	ion mass of: 5-chloro I-isothiazolin-3-one a yl-2H -isothiazol-3- c	and 2-	55965-84-9 613-167-00-5 01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071	>= 0,0002 - 0,0015
				M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100	
				specific concentration limit Skin Corr. 1C; H314 >= 0,6 % Skin Irrit. 2; H315	

according to Regulation (EC) No. 1907/2006



SPEKTRA RENOXAN FACADE PAINT

Version 1.0			Date of last issue: - Date of first issue: 29.01.2021	
			0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 >= 0,0015 % Eye Dam. 1; H318 >= 0,6 %	
Subst	ances with a workpl	ace exposure limit :		
	z (SiO2)	14808-60-7 238-878-4		>= 1 - < 10
Talc		14807-96-6 238-877-9 01-2120140278-5	8	>= 1 - < 10

SECTION 4: First aid measures

4.1 Description of first aid measures General advice : Do not leave the victim unattended. If inhaled If breathed in, move person into fresh air. : In case of skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. In case of eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention. If swallowed Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. 4.2 Most important symptoms and effects, both acute and delayed Risks May cause an allergic skin reaction. : May cause an allergic skin reaction. 4.3 Indication of any immediate medical attention and special treatment needed Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

according to Regulation (EC) No. 1907/2006



SPEKTRA RENOXAN FACADE PAINT

Version 1.0	Revision Date: 29.01.2021		Number: 0GA00_116 EN	Date of last issue: - Date of first issue: 29.01.2021
			Use water spray, a bon dioxide.	cohol-resistant foam, dry chemical or car-
5.2 Spe	cial hazards arising f	rom th	e substance or mixt	ure
Hazardous combustion prod- : ucts			No hazardous com	bustion products are known
5.3 Advi	ice for firefighters			
•	ecial protective equipm firefighters	ent :	Wear self-containe essary.	d breathing apparatus for firefighting if nec-
Fur	ther information	:		oes not burn. e for chemical fires. to cool fully closed containers.
SECTIO	ON 6: Accidental re	lease	measures	
6.1 Pers	onal precautions, pr	otectiv	e equipment and er	nergency procedures
	sonal precautions		Avoid contact with	

Personal precautions	: Avoid contact with skin and eyes.
	Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so.

6.2 Environmental precautions

Environmental precautions	Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform
	respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel,
		acid binder, universal binder, sawdust).
		Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling		
Advice on safe handling :	:	No special technical protective measures required. For personal protection see section 8.
Advice on protection against : fire and explosion	:	Normal measures for preventive fire protection.
Hygiene measures :	:	When using do not eat, drink or smoke. Wash thoroughly after handling.

according to Regulation (EC) No. 1907/2006



SPEKTRA RENOXAN FACADE PAINT

Version 1.0	Revision Date: 29.01.2021	SDS Number: MAT0GA00_116 GB / EN	Date of last issue: - Date of first issue: 29.01.2021
1.0	20.01.2021		

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	:	Containers which are opened must be carefully resealed and kept upright to prevent leakage. Perishable if frozen. To main- tain product quality, do not store in heat or direct sunlight.
Advice on common storage	:	No materials to be especially mentioned.
Further information on stor- age stability	:	Protect from frost.
3 Specific and use(s)		

7.3 Specific end use(s)

Specific use(s)

: Consult the technical guidelines for the use of this substance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Calcium carbonate	471-34-1	TWA (inhalable dust)	10 mg/m3	GB EH40
		TWA (Respirable dust)	4 mg/m3	GB EH40
limestone	1317-65-3	TWÁ (inhalable dust)	10 mg/m3	GB EH40
		TWA (Respirable dust)	4 mg/m3	GB EH40
titanium dioxide	13463-67-7	TWA (inhalable dust)	10 mg/m3	GB EH40
		TWÁ (Respirable dust)	4 mg/m3	GB EH40
Quartz (SiO2)	14808-60-7	TWÁ (Respirable dust)	0,1 mg/m3	2004/37/EC
	Further inform	hation: Carcinogens	or mutagens	
		TWA (Respirable fraction)	0,1 mg/m3 (Silica)	GB EH40
	Further inform age.	nation: Capable of ca	ausing cancer and/or herit	able genetic dam-
Talc	14807-96-6	TWA (Respirable dust)	1 mg/m3	GB EH40
		TWA (Respirable dust)	0,1 mg/m3	2004/37/EC
	Further inform	hation: Carcinogens	or mutagens	
Mica	12001-26-2	TWA (Inhalable)	10 mg/m3	GB EH40
		TWA (Respirable fraction)	0,8 mg/m3	GB EH40

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

according to Regulation (EC) No. 1907/2006



SPEKTRA RENOXAN FACADE PAINT

	Revision Date: 29.01.2021	SDS Numbo MAT0GA00 GB / EN		te of last issue: - te of first issue: 29.01.20)21
Substand	ce name	End Use	Exposure routes	Potential health ef- fects	Value
Calcium	carbonate	Workers	Inhalation	Long-term local ef- fects	4,26 mg/m3
		Consumers	Inhalation	Long-term local ef- fects	1,06 mg/m3
titanium o	dioxide	Workers	Inhalation	Long-term local ef- fects	10 mg/m3
		Consumers	Oral	Long-term systemic effects	700 mg/kg bw/day
Talc		Workers	Inhalation	Acute systemic ef- fects	2,16 mg/m3
		Workers	Inhalation	Acute local effects	3,6 mg/m3
		Consumers	Inhalation	Acute systemic ef- fects	1,08 mg/m3
		Consumers	Inhalation	Acute local effects	1,8 mg/m3
		Consumers	Dermal	Long-term local ef- fects	2,27 mg/cm
		Workers	Dermal	Long-term local ef- fects	4,54 mg/cm
		Consumers	Oral	Long-term systemic effects	160 mg/kg bw/day
		Consumers	Oral	Acute systemic ef- fects	160 mg/kg bw/day
		Workers	Dermal	Long-term systemic effects	43,2 mg/kg bw/day
		Consumers	Dermal	Long-term systemic effects	21,6 mg/kg bw/day
1,2-benz 3(2H)-on	isothiazol- e	Workers	Inhalation	Long-term systemic effects	6,81 mg/m3
		Workers	Dermal	Long-term systemic effects	0,966 mg/k bw/day
		Consumers	Inhalation	Long-term systemic effects	1,2 mg/m3
		Consumers	Dermal	Long-term systemic effects	0,345 mg/k bw/day
chloro-2- isothiazo 2-methyl-	mass of: 5- methyl-4- lin-3-one and -2H - l-3- one (3:1)	Consumers	Inhalation	Acute local effects	0,04 mg/m3
	Workers	Inhalation	Long-term local ef- fects	0,02 mg/m3	
		Workers	Inhalation	Acute local effects	0,04 mg/m3
		Consumers	Inhalation	Long-term local ef- fects	0,02 mg/m3
		Consumers	Oral	Long-term systemic effects	0,09 mg/kg bw/day
		Consumers	Oral	Acute systemic ef- fects	0,11 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

according to Regulation (EC) No. 1907/2006



SPEKTRA RENOXAN FACADE PAINT

Version 1.0 Revision Date: 29.01.2021

SDS Number: MAT0GA00_116 GB / EN Date of last issue: -Date of first issue: 29.01.2021

Substance name	Environmental Compartment	Value
Calcium carbonate	Sewage treatment plant	100 mg/l
titanium dioxide	Soil	100 mg/kg dry
		weight (d.w.)
	Marine water	0,0184 mg/l
	Fresh water	0,184 mg/l
	Marine sediment	100 mg/kg dry
		weight (d.w.)
	Fresh water sediment	1000 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0,193 mg/l
Talc	Marine water	141,26 mg/l
	Fresh water	597,97 mg/l
	Marine sediment	3,13 mg/kg dry
		weight (d.w.)
	Fresh water sediment	31,33 mg/kg dry
		weight (d.w.)
	Intermittent use/release	597,97 mg/l
1,2-benzisothiazol-3(2H)-one	Fresh water	0,00403 mg/l
	Intermittent use/release	0,0011 mg/l
	Marine water	0,000403 mg/l
	Sewage treatment plant	1,03 mg/l
	Fresh water sediment	0,0499 mg/kg dry
		weight (d.w.)
	Marine sediment	0,00499 mg/kg
		dry weight (d.w.)
	Soil	3 mg/kg dry
		weight (d.w.)
reaction mass of: 5-chloro-2-	Soil	0,01 mg/kg dry
methyl-4-isothiazolin-3-one and		weight (d.w.)
2-methyl-2H -isothiazol-3- one		
(3:1)		
	Marine water	0,00339 mg/l
	Fresh water	0,00339 mg/l
	Marine sediment	0,027 mg/kg dry
		weight (d.w.)
	Fresh water sediment	0,027 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	0,23 mg/l
	Intermittent use/release	0,00339 mg/l

8.2 Exposure controls

Personal protective equipment

Eye protection: GogglesHand protection
Material
Glove thickness
Protective index: Nitrile rubber
0,2 mm
: Class 3

according to Regulation (EC) No. 1907/2006



SPEKTRA RENOXAN FACADE PAINT

Version 1.0	Revision Date: 29.01.2021	SDS Number: MAT0GA00_116 GB / EN	Date of last issue: - Date of first issue: 29.01.2021
R	emarks	: Wear suitable gl	oves.
Skin	and body protection		othing otection according to the amount and con- dangerous substance at the work place.
Resp	iratory protection	: No personal resp quired.	piratory protective equipment normally re-

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

	Physical state	:	liquid
	Colour	:	in accordance with the product description
	Odour	:	No information available.
	Odour Threshold	:	No data available
	Flammability	:	Not applicable
	Flash point	:	Not applicable
	рН	:	No data available
	Viscosity Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)
	Solubility(ies) Water solubility	:	completely miscible
	Solubility in other solvents	:	No data available
	Partition coefficient: n- octanol/water	:	No data available
	Density	:	1,45 - 1,50 g/cm3
9.2 VOC	Other information	(Directi 18 g/l	ive 2004/42/EC)

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

according to Regulation (EC) No. 1907/2006





Version 1.0	Revision Date: 29.01.2021	SDS Number: MAT0GA00_116 GB / EN	Date of last issue: - Date of first issue: 29.01.2021			
	10.2 Chemical stability Stable under recommended storage conditions.					
10.3 Poss	ibility of hazardous	s reactions				
Hazaı	rdous reactions	: No data availat	ble			
	litions to avoid	: Protect from fro	ost, heat and sunlight.			
	npatible materials ials to avoid	•	ith oxidizing agents. ith strong acids and bases.			

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

Zinc pyridinethione:

:	Assessment: The component/mixture is toxic after single in- gestion.	
	LD50 Oral (Rat): > 177 mg/kg	
:	Test atmosphere: vapour Assessment: The component/mixture is toxic after short term inhalation.	
:	LD50 (Rat): > 2.000 mg/kg	
:	Assessment: The component/mixture is moderately toxic after single ingestion.	
	LD50 Oral (Rat): >= 318 mg/kg	
:	Test atmosphere: vapour Assessment: The component/mixture is toxic after short term inhalation.	
:	Assessment: The component/mixture is toxic after single con- tact with skin.	
	:	

according to Regulation (EC) No. 1907/2006





ersion)	Revision Date: 29.01.2021		Number:Date of last issue: -DGA00_116Date of first issue: 29.01.2021EN
			LD50 (Rabbit): >= 311 mg/kg
	enzisothiazol-3(2H) oral toxicity)-one: :	Assessment: The component/mixture is moderately toxic after single ingestion.
2-met	thylisothiazol-3(2H)-one:	
Acute	e oral toxicity	:	Assessment: The component/mixture is toxic after single in- gestion.
Acute	inhalation toxicity	:	Test atmosphere: vapour Assessment: The component/mixture is highly toxic after shor term inhalation.
Acute	e dermal toxicity	:	Assessment: The component/mixture is toxic after single con- tact with skin.
Not cl	corrosion/irritation lassified based on a ponents:	-	information.
octhi Resul	linone (ISO): It	:	Corrosive after 3 minutes to 1 hour of exposure
1,2-b Resul	enzisothiazol-3(2H) It)-one: :	irritating
2-me t Resul	thylisothiazol-3(2H It)-one: :	Corrosive after 3 minutes to 1 hour of exposure
	ous eye damage/eye lassified based on a		
Com	ponents:		
ا Zinc Resul	pyridinethione: It	:	Corrosive
1,2-b o Resul	enzisothiazol-3(2H) ^{It})-one: :	Corrosive
Resp	iratory or skin sen	sitisatio	on
-	sensitisation cause an allergic ski	n reactio	on.

according to Regulation (EC) No. 1907/2006



SPEKTRA RENOXAN FACADE PAINT

Version 1.0	Revision Date: 29.01.2021	SDS Number: MAT0GA00_116 GB / EN	Date of last issue: - Date of first issue: 29.01.2021				
	spiratory sensitisatio						
	omponents:	allable information.					
	thilinone (ISO): sult	: Probability or evic	lence of skin sensitisation in humans				
1,2	-benzisothiazol-3(2H)	-one:					
Re	sult	: Probability or evid	lence of skin sensitisation in humans				
2-r	nethylisothiazol-3(2H)	-one:					
	esult		lence of skin sensitisation in humans				
Ge	erm cell mutagenicity						
No	t classified based on av	vailable information.					
	Carcinogenicity Not classified based on available information.						
	Reproductive toxicity Not classified based on available information.						
	STOT - single exposure Not classified based on available information.						
	OT - repeated exposu It classified based on av						
As	piration toxicity						
No	t classified based on av	vailable information.					
11.2 Inf	ormation on other ha	zards					
En	docrine disrupting pr	operties					
Pro	oduct:						
As	sessment	ered to have endo REACH Article 57	Exture does not contain components consid- borine disrupting properties according to (f) or Commission Delegated regulation or Commission Regulation (EU) 2018/605 at higher.				
SECTI	ON 12: Ecological ir	nformation					
12.1 To	vicity						
	omponents:						

Components:

Zinc pyridinethione:

Toxicity to fish

: LC50 (Pimephales promelas (fathead minnow)): >= 0,0026

according to Regulation (EC) No. 1907/2006



SPEKTRA RENOXAN FACADE PAINT

Version 1.0	Revision Da 29.01.2021		Т0	Number:Date of last issue: -IGA00_116Date of first issue: 29.01.2021EN
				mg/l Exposure time: 96 h
	cicity to daphnia a atic invertebrates		:	EC50 (Daphnia (water flea)): >= 0,0028 mg/l Exposure time: 48 h
Tox plai	icity to algae/aqu nts	atic	:	ErC50 (Desmodesmus subspicatus (green algae)): >= 0,028 mg/l Exposure time: 120 h
M-F icity	actor (Acute aqu /)	atic tox-	:	100
	actor (Chronic ac city)	quatic	:	10
	otoxicology Asso ite aquatic toxicity			Very toxic to aquatic life.
	onic aquatic toxic		:	Very toxic to aquatic life with long lasting effects.
	hilinone (ISO): icity to fish		:	LC50 (Oncorhynchus mykiss (rainbow trout)): >= 0,047 mg/l Exposure time: 96 h
				LC50 (Lepomis macrochirus (Bluegill sunfish)): >= 0,18 mg/l Exposure time: 96 h
	icity to daphnia a atic invertebrates		:	EC50 (Daphnia (water flea)): >= 0,32 mg/l Exposure time: 48 h
Tox plai	cicity to algae/aqu	atic	:	EC50 (algae): >= 0,031 mg/l Exposure time: 72 h
	otoxicology Asso ite aquatic toxicity		:	Very toxic to aquatic life.
Chr	onic aquatic toxic	city	:	Very toxic to aquatic life with long lasting effects.
1,2	-benzisothiazol-3	3(2H)-one	:	
	otoxicology Assertion aquatic toxic		:	Toxic to aquatic life with long lasting effects.
	nethylisothiazol- Factor (Acute aqu /)		:	10
M-F	actor (Chronic ad	quatic	:	1

according to Regulation (EC) No. 1907/2006



SPEKTRA RENOXAN FACADE PAINT

Version 1.0	Revision Date: 29.01.2021		Number: DGA00_116 EN	Date of last issue: - Date of first issue: 29.01.2021			
toxi	city)						
Ecc	otoxicology Assessm	ent					
Acu	te aquatic toxicity	:	Very toxic to aquation	c life.			
	reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol one (3:1):						
Тох	icity to fish	:	LC50 (Salvelinus na Exposure time: 96 h	amaycush (lake trout)): >= 10,85 mg/l ח			
Tox plar	icity to algae/aquatic hts	:	LC50 (algae): >= 0, Exposure time: 48 h				
			LC50 (algae): 0,018 Exposure time: 72 h				
M-F icity	actor (Acute aquatic to	ox- :	100				
	actor (Chronic aquatic city)	; ;	100				
12.2 Per	12.2 Persistence and degradability						
<u>Cor</u>	nponents:						
	ethylisothiazol-3(2H) degradability	-one: :	Result: Biodegradal	ble			
12.3 Bio	accumulative potent	ial					
<u>Cor</u>	<u>nponents:</u>						
Par	benzisothiazol-3(2H) tition coefficient: n- anol/water	-one: :	log Pow: 1,3				
	bility in soil data available						
12.5 Res	sults of PBT and vPv	B asse	ssment				
	<u>duct:</u> essment	:	to be either persiste	ture contains no components considered ent, bioaccumulative and toxic (PBT), or very bioaccumulative (vPvB) at levels of			

according to Regulation (EC) No. 1907/2006





VersionRevision Date:SDS Number:Date of last issue: -1.029.01.2021MAT0GA00_116
GB / ENDate of first issue: 29.01.2021

12.6 Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods	t methods	treatment	Waste	13.1
------------------------------	-----------	-----------	-------	------

Product	:	Do not release the product to the aquatic environment
Contaminated packaging	:	Empty containers should be taken to an approved waste han- dling site for recycling or disposal.
Waste Code	:	08 01 20, aqueous suspensions containing paint or varnish other than those mentioned in 08 01 19

SECTION 14: Transport information

14.1 UN number or ID number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Regulation (EC) No. 1907/2006



SPEKTRA RENOXAN FACADE PAINT

Vers 1.0	sion	Revision Date: 29.01.2021		Number: IGA00_116 EN	_		of last issue: - of first issue: 29.01.2021
	the ma	H - Restrictions on t rket and use of cert ations and articles (:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3		
	ment a	tion (EC) No 649/20 nd the Council conc gerous chemicals	ť	:	Not applicable		
		H - Candidate List o			:	Not applicable	
	REACH - List of substances subject to authorisation (Annex XIV)						Not applicable
	Regulation (EC) No 1005/2009 on substances that de- plete the ozone layer						Not applicable
	Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)						Not applicable
	Seveso III: Directive 2012/18/EU of the Euro- pean Parliament and of the Council on the control of major-accident hazards involving dangerous substances.						applicable
	Volatile	organic compound	s :	Directive 2004/42/E Volatile organic com	-	und	s (VOC) content: 18 g/l

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H301 :	Toxic if swallowed.
H302 :	Harmful if swallowed.
H310 :	Fatal in contact with skin.
H311 :	Toxic in contact with skin.
H314 :	Causes severe skin burns and eye damage.
H315 :	Causes skin irritation.
H317 :	May cause an allergic skin reaction.
H318 :	Causes serious eye damage.
H330 :	Fatal if inhaled.
H331 :	Toxic if inhaled.
H351 :	Suspected of causing cancer if inhaled.
H400 :	Very toxic to aquatic life.

according to Regulation (EC) No. 1907/2006



SPEKTRA RENOXAN FACADE PAINT

Version 1.0	Revision Date: 29.01.2021		Number:)GA00_116 EN	Date of last issue: - Date of first issue: 29.01.2021	
H410 H411 EUH07		: : :	Toxic to aquatic life v Corrosive to the resp	life with long lasting effects. vith long lasting effects. iratory tract.	
	kt of other abbrev	lations			
Acute 7		:	Acute toxicity		
Aquatic Acute		:	Short-term (acute) aquatic hazard		
Aquatic Chronic			Long-term (chronic) aquatic hazard		
Carc.		:	Carcinogenicity		
Eye Dam.		:	Serious eye damage		
Skin Co	orr.	:	Skin corrosion		
Skin Irr	it.	:	Skin irritation		
Skin Se	ens.	:	Skin sensitisation		
2004/3	7/EC	:	Europe. Directive 20	04/37/EC on the protection of workers	
				to exposure to carcinogens or mutagens	
GB EH	40	:	UK. EH40 WEL - Wo	rkplace Exposure Limits	
2004/3	7/EC / TWA	:	Long term exposure		
	40 / TWA	:	e 1	limit (8-hour TWA reference period)	

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP -Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL -International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS -Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

according to Regulation (EC) No. 1907/2006



SPEKTRA RENOXAN FACADE PAINT

Version 1.0	Revision Date: 29.01.2021	SDS Number: MAT0GA00_116 GB / EN	Date of last issue: - Date of first issue: 29.01.2021
Class	ification of the mix	xture:	Classification procedure:
Skin S	Sens. 1	H317	Calculation method
Aquatic Chronic 3		H412	Calculation method
Material codes (bulk) for which the SDS is valid		401710;401711;	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.